





ERZ-HPA-0790-0840-46

The ERZ-HPA-0790-0840-46 is a High Power Amplifier providing an output power of 46 dBm and a gain of 54 dB. The compact size and modularity makes it ideal for a wide range of applications.

Main Features:

- Frequency Range: 7.9 to 8.4 GHz.
- Typical values: Psat 46 dBm, Gain 42 dB
- RF connectors (I/O): SMA Female
- TTL ON/OFF Control
- · Power, current and temperature monitoring
- Compact aluminum housing
- Hi-reliability and dedicated screening/ environmental tests available under request

Typical applications:

- Industrial / Laboratory
- Satcom / Telecom
- Space / Aerospace / Military

Parameter		Units		
	Min	Тур	Max	
Frequency	7.9	-	8.4	GHz
Saturated Output Power (CW) (dBm)	45	45.5	46	dB
Small Signal Gain	53	54	55	dB
Gain Flatness	-	±1	-	dB
Switch ON/OFF Time	-	200/200	-	ns
VSWR input	-	-	1.5:1	-
VSWR output	-	-	1.5:1	-
DC Voltage	18	24	36	V
Power Consumption @Psat	-	200	220	W
Power Consumption @Disable mode	-	5	8	W
RF Connectors	SMA Female IN/OUT			-

Performance

Specifications at case temperature of 25°C



Output Power

Figure 1 shows saturated output power measurement (CW) as a function of frequency at room temperature values 25°C, 70°C and -40°C.



Figure 1: ERZ-HPA-0790-0840-46 Psat

Small Signal Gain

Figure 2 shows small signal gain measurement as a function of frequency at room temperatura values 25°C, 70°C and -40°C.





Tel: +34 942 29 13 42



Input and Output Matching

Figure 3 and Figure 4 show input and output VSWR as a function of frequency at room temperature (25°C).



Figure 3: ERZ-HPA-0790-0840-46 Input Matching





Tel: +34 942 29 13 42



ERZ-HPA-0790-0840-46

Switch ON/OFF Time

Figure 5 and Figure 6 show switch ON/OFF time



Figure 5: ERZ-HPA-0790-0840-46 Switch ON Time



Figure 6: ERZ-HPA-0790-0840-46 Switch OFF Time



Output Power Detector

Figure 7 shows output power detector voltage versus output power at different frequencies.



Figure 7: ERZ-HPA-0790-0840-46 Output power detector

Figure 2: ERZ-HPA-0790-0840-46 Small Signal Gain

Tel: +34 942 29 13 42



High Power Amplifier

ERZ-HPA-0790-0840-46

Mechanics and Housing





High Power Amplifier

ERZ-HPA-0790-0840-46

External Electrical Interface

- DC and Control: DSUB 7W2 Male type connector
- RF input and output: SMA Female



Pin No.	Label	Function	Description
A1	VDD	VDD	+(1836) VDC
A2	PGND	Power Ground	Power Ground
1	EN	Enable	TTL Signal OFF (0V to 0.8V); ON (2V to 5.5V))
2	TEMP	Temperature Monitor	Vo = -11.69 mV C × T + 1.8663 V
3	I_SEN	Current Sensor	Vo= 0.1V/A
4	DET	Output Power Detector	Vo=1.2V @ Pout=37dBm, Vo=1.75V @ Pout=40dBm, Vo=2.5V @ Pout=43dBm, Vo=3.6V @ Pout=46dBm
5	GND	Ground	Ground

Dimensions and Weight

- Dimensions: 180x120x22 mm
- Weight: 860 grams.

Tel: +34 942 29 13 42



ERZ-HPA-0790-0840-46

Absolute Maximum Ratings

Condition	Value	
DC Voltage	+36 VDC	
Maximum Input Power	+10 dBm @CW	
Enable Control Voltage	+5.5 VDC	
Operation temperature (at case)	-40 to 70 °C	
Storage temperature	-55 to 125 °C	

- Stress above these ratings may cause permanent damage to the device.
- It is final user responsibility to maintain the amplifier within the specified ranges.
- Note: Operation at +25°C with an output power in modulation or CW conditions higher than 44 dBm is not recommended. For an output power higher than 44 dBm the recommended operation is under pulse conditions (pulse width 100us and duty cycle 10%).



Measurements Conditions

All measurements provided in this report were performed at the following conditions:

Condition	Value
Temperature (DUT ON)	25 °C ± 1°C
Humidity	44% ± 10%
DUT Warm up time	30 min
DUT minimum operation time	24 hours
Test equipment warm up time	2 hours
Additional temperature cycles in climatic chamber (DUT OFF)	-40°C to 85°C

Environmental Specifications (By Design)

Operating Temperature:	
Storage Temperature:	
Vibration:	
Shock:	
Acceleration:	

-40 to +85 °C -55 to 125 °C 8g rms 20g,11ms,saw-tooth 15g (MIL-STD-810F, method 520.2) (MIL-STD-810F, method 520.2) (MIL-STD-810F, method 514.5) (MIL-STD-810F, method 516.5) (MIL-STD-810F, method 513.5)

Tel: +34 942 29 13 42



High Power Amplifier

ERZ-HPA-0790-0840-46

Documentation and Test Reports

All modules are at least delivered with: Electrical Test Report, Certificate of Conformance, Certificate of Acceptance and Origin. Optionally, units can be environmentally tested (temperature, vibration...).

Option (HS): Heat Sink

A heat sink (HS) can be provided to allow the operation of Power Amplifiers. Please note that most power amplifiers need heat sink or appropriate heat dissipation strategy.

Space / Military Usage

Most of ERZIA's products are based on rad-hard technologies and can be manufactured and integrated according to MIL / ECSS or specific hi-rel standard-screening for space, aeronautics, military or specific hi-reliability usage.

Customization and Extended Performances

ERZIA can fully design or adapt one of the existing RF amplifiers designs according to your specifications. Please contact us for additional information.

Model Number Codification

MODEL NUMBER



Tel: +34 942 29 13 42

ERZIA

20241018_rev2.0

Copyright © 2020 ERZIA Technologies S.L. All rights reserved. This information is commercial and indicative, subject to change without notice

Tel: +34 942 29 13 42

sales@erzia.com

www.erzia.com