



### Main Features:

- Frequency Range: 33 to 45 GHz.
- Typical values: Pout 23 dBm, Gain 15 dB
- RF connectors (I/O): 2.4 mm Female
- Solder filtered pins for DC connection
- Several mounting options
- Gold plated compact aluminum housing
- Hi-reliability and dedicated screening/ environmental tests available under request

### ERZ-HPA-3300-4500-23

The ERZ-HPA-3300-4500-23 is a High Power Amplifier providing an output power of 23 dBm and a gain of 15 dB. The compact size and modularity makes it ideal for a wide range of applications.

### Typical applications:

- Industrial / Laboratory
- Satcom / Telecom
- Space / Aerospace / Military

### Performance

Parameter	Value			Units
	Min	Typ	Max	
Frequency	33	-	45	GHz
Output Power (P1dB)	20	23	26	dBm
Small Signal Gain	13	15	19	dB
Gain Flatness	-	±2.5	-	dB
Noise Figure	-	-	-	dB
VSWR input	-	3.5:1	9.0:1	-
VSWR output	-	2.0:1	3.5:1	-
DC Voltage	10	12	14	V
Power Consumption	-	2.5	-	W
RF Connectors	2.4 mm Female IN/OUT			-

Specifications at case temperature of 25°C

### Output Power

Figure 1 shows output power at 1dB compression measurement as a function of frequency at room temperature (25°C).




Figure 1: ERZ-HPA-3300-4500-23 P1dB

### Small Signal Gain

Figure 2 shows small signal gain measurement as a function of frequency at room temperature (25°C).




Figure 2: ERZ-HPA-3300-4500-23 Small Signal Gain

### Absolute Maximum Ratings

Condition	Value
DC Voltage	+16 VDC
Maximum Input Power (CW)	20 dBm
Operation temperature (at case)	-35 to 75 °C
Storage temperature	-55 to 125 °C

- Stress above these ratings may cause permanent damage to the device.
- It is final user responsibility to maintain the amplifier within the specified ranges.

### Measurements Conditions

All measurements provided in this report were performed at the following conditions:

Condition	Value
Temperature (DUT ON)	25 °C ± 1°C
Humidity	44% ± 10%
DUT Warm up time	30 min
DUT minimum operation time	24 hours
Test equipment warm up time	2 hours
Additional temperature cycles in climatic chamber (DUT OFF)	-40°C to 85°C

### Environmental Specifications (By Design)


Operating Temperature:	-35 to +75 °C	(MIL-STD-810F, method 520.2)
Storage Temperature:	-55 to 125 °C	(MIL-STD-810F, method 520.2)
Vibration:	8g rms	(MIL-STD-810F, method 514.5)
Shock:	20g,11ms,saw-tooth	(MIL-STD-810F, method 516.5)
Acceleration:	15g	(MIL-STD-810F, method 513.5)

### RoHS & REACH Compliance

This part is compliant with EU 2011/65/UE RoHS (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) and REACH (Registration, Evaluation, Authorization and restriction of Chemical substances) directives.



## Mechanics and Housing



DENOMINACIÓN / TITLE	
M1 R1	
FORMA / SE	CAGE CODE
A	8820B
ESCALA / SCALE	IV PLANO DRAWING
00	ERZ-HPA_00
1 OF 1	1 OF 1

DEJADO EN BLANCO	FECHAS DE
DESARROLLO	000000
COMPROMISO	000000
PROBADO	000000
CONTR. NUM.	000000
USADO EN	PROYECT
INTERVALO	NA
MUSI. INC.	NA
MUSI. INC.	NA

Dimensiones en mm (in). Dimensiones en pulgadas.

TOLENCIAS GENERALES SIN UNIDAD GENERAL TOLERANCES PANDORA

ARISTAS LIMPADAS CON RAJAS 0,075 mm. O CHARLANES DE ELIMINAR ARISTAS LIMPADAS CON RAJAS 0,075 mm. O CHARLANES DE ELIMINAR

RECORRIDO SUPERFICIAL SUPERFICIAL FINISH

## Documentation and Test Reports

All modules are at least delivered with: Electrical Test Report, Certificate of Conformance, Certificate of Acceptance and Origin. Optionally, units can be environmentally tested (temperature, vibration...).

## Option (HS): Heat Sink

A heat sink (HS) can be provided to allow the operation of Power Amplifiers. Please note that most power amplifiers need heat sink or appropriate heat dissipation strategy.

## Space / Military Usage


Most of ERZIA's products are based on rad-hard technologies and can be manufactured and integrated according to MIL / ECSS or specific hi-rel standard-screening for space, aeronautics, military or specific hi-reliability usage.

## Customization and Extended Performances

ERZIA can fully design or adapt one of the existing RF amplifiers designs according to your specifications. Please contact us for additional information.

## Model Number Codification

### MODEL NUMBER



# ERZIA

20190130\_rev1.0

Copyright © 2019 Erzia Technologies. All rights reserved. This information is commercial and indicative, subject to change without notice

Tel: +34 942 29 13 42

[sales@erzia.com](mailto:sales@erzia.com)

[www.erzia.com](http://www.erzia.com)