



### Main Features:

- Frequency Range: 30 to 40 GHz.
- Typical values: Psat 33 dBm, Gain 39 dB
- RF connectors (I/O): 2.92 mm (F) / WR28
- Solder filtered pins for DC connection
- Several mounting options
- Gold plated compact aluminum housing
- Hi-reliability and dedicated screening/ environmental tests available under request

### ERZ-HPA-3000-4000-32-E-W

The ERZ-HPA-3000-4000-32-E-W is a High Power Amplifier providing an output power of 33 dBm and a gain of 39 dB. The compact size and modularity makes it ideal for a wide range of applications.

### Typical applications:

- Industrial / Laboratory
- Satcom / Telecom
- Space / Aerospace / Military

### Performance

Parameter	Value			Units
	Min	Typ	Max	
Frequency	30	-	40	GHz
Output Power (Psat)	31	33	35	dBm
Small Signal Gain	36	39	42	dB
Gain Flatness	-	±2	-	dB
Noise Figure	-	-	-	dB
VSWR input	1.1:1	1.3:1	1.6:1	-
VSWR output	2.0:1	2.5:1	3.5:1	-
DC Voltage	10	12	14	V
Power Consumption	-	11 @P1dB 18 @Psat	-	W
RF Connectors	2.92 Female IN / WR28 OUT			-

Specifications at case temperature of 25°C

### Saturated Output Power

Figure 1 shows the saturated output power measured as a function of frequency at room temperature (25°C).




Figure 1: ERZ-HPA-3000-4000-32-E-W Psat

### Small signal gain

Figure 2 shows the S-parameters measured as a function of frequency at different temperatures.




Figure 2: ERZ-HPA-3000-4000-32-E-W Small Signal Gain

### Input and Output matching

Figure 3 shows input and output VSWR a function of frequency at room temperature (25°C).




Figure 3: ERZ-HPA-3000-4000-32-E-W Input and Output Matching

### Absolute Maximum Ratings

Condition	Value
DC Voltage	14 VDC
Maximum Input Power (CW)	0 dBm
Operation temperature (at case)	-40 to 85°C
Storage temperature	-55 to 125°C

- Stress above these ratings may cause permanent damage to the device.
- It is final user responsibility to maintain the amplifier within the specified ranges.

### Measurements Conditions

All measurements provided in this report were performed at the following conditions:

Condition	Value
Temperature (DUT ON)	-35°C, 25°C, 70°C ± 1°C
Humidity	44% ± 10%
DUT Warm up time	30 min
DUT minimum operation time	24 hours
Test equipment warm up time	2 hours
Additional temperature cycles in climatic chamber (DUT OFF)	-40°C to 85°C

### Environmental Specifications (By Design)

Operating Temperature:	-40 to +85 °C	(MIL-STD-810F, method 520.2)
Storage Temperature:	-55 to 125 °C	(MIL-STD-810F, method 520.2)
Vibration:	8g rms	(MIL-STD-810F, method 514.5)
Shock:	20g, 11ms, saw-tooth	(MIL-STD-810F, method 516.5)
Acceleration:	15g	(MIL-STD-810F, method 513.5)

### RoHS & REACH Compliance

This part is compliant with EU 2011/65/UE RoHS (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) and REACH (Registration, Evaluation, Authorization and restriction of Chemical substances) directives.





### Documentation and Test Reports

All modules are at least delivered with: Electrical Test Report, Certificate of Conformance, Certificate of Acceptance and Origin. Optionally, units can be environmentally tested (temperature, vibration...).

### Option (HS): Heat Sink

A heat sink (HS) can be provided to allow the operation of Power Amplifiers. Please note that most power amplifiers need heat sink or appropriate heat dissipation strategy.

### Space / Military Usage


Most of ERZIA's products are based on rad-hard technologies and can be manufactured and integrated according to MIL / ECSS or specific hi-rel standard-screening for space, aeronautics, military or specific hi-reliability usage.

### Customization and Extended Performances

ERZIA can fully design or adapt one of the existing RF amplifiers designs according to your specifications. Please contact us for additional information.

### Model Number Codification

#### MODEL NUMBER



# ERZIA

20210416\_rev1.0

Copyright © 2021 ERZIA Technologies. All rights reserved. This information is commercial and indicative, subject to change without notice

Tel: +34 942 29 13 42

[sales@erzia.com](mailto:sales@erzia.com)

[www.erzia.com](http://www.erzia.com)