ERZIA
DATASHEET

Low Noise Amplifier

ERZ-LNA-2400-4400-23-2.5

Main Features:

- Frequency Range: 24 to 44 GHz.
- Typical values: Gain 23 dB, NF 2.5 dB
- RF connectors (I/O): 2.92 mm Female
- Solder filtered pins for DC connection
- Several mounting options
- Gold platted compact aluminum housing
- Hi-reliability and dedicated screening/ environmental tests available under request

ERZ-LNA-2400-4400-23-2.5

The ERZ-LNA-2400-4400-23-2.5 is a Low Noise Amplifier providing a gain of 23 dB with a noise figure of 2.5 dB. The compact size and modularity makes it ideal for a wide range of applications.

Typical applications:

- Industrial / Laboratory
- Satcom / Telecom
- Space / Aerospace

Performance

Parameter	Value			Units
	Min	Typ	Max	
Frequency	24	-	44	GHz
Output Power (P1dB)	3.8	6.0	7.5	dBm
Small Signal Gain	22	23	26	dB
Gain Flatness	-	±1	-	dB
Noise Figure	-	2.5	3	dB
VSWR input	-	1.6:1	-	-
VSWR output	-	1.4:1	-	-
DC Voltage	9	12	15	V
Power Consumption	-	0.2	-	W
RF Connectors	2.92 mm Female IN/OUT			-

Specifications at a case temperature of 25°C at 12 V

P1dB

Figure 1 shows P1dB measurement as a function of frequency at room temperature (25°C).



Figure 1: ERZ-LNA-0200-2400-15-3 Saturation Power

Small Signal Gain

Figure 2 shows the small signal gain measurement as a function of frequency at room temperature (25°C).



Figure 2: Figure 1: ERZ-LNA-0200-2400-15-3 Small Signal Gain

Noise Figure

Figure 3 shows the noise figure measurement as a function of frequency at room temperature (25°C).



Figure 3: ERZ-LNA-0200-2400-15-3 Noise Figure

Absolute Maximum Ratings

Condition	Value
DC Voltage	+15 VDC
Maximum Input Power (CW)	15 dBm
Operation temperature (at case)	-55 to 85 °C
Storage temperature	-65 to 150 °C

- Stress above these ratings may cause permanent damage to the device.
- It is final user responsibility to maintain the amplifier within the specified ranges.

Environmental Specifications (By Design)

Operating Temperature:	-45 to +85 °C	(MIL-STD-810F, method 520.2)
Storage Temperature:	-55 to 125 °C	(MIL-STD-810F, method 520.2)
Vibration:	8g rms	(MIL-STD-810F, method 514.5)
Shock:	20g,11ms,saw-tooth	(MIL-STD-810F, method 516.5)
Acceleration:	15g	(MIL-STD-810F, method 513.5)

RoHS & REACH Compliance

This part is compliant with EU 2011/65/UE RoHS (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) and REACH (Registration, Evaluation, Authorization and restriction of Chemical substances) directives.

ERZIA
DATASHEET

Low Noise Amplifier

ERZ-LNA-2400-4400-23-2.5

Mechanics and Housing



Parameter	Value
Size	16x30x17.5 mm
Weight	21 grams ±10%
RF Input Connector	SMA Female
RF Output Connector	SMA Female
DC Connector	Filtered pins

Documentation and Test Reports

All modules are at least delivered with: Electrical Test Report, Certificate of Conformance, Certificate of Acceptance and Origin. Optionally, units can be environmentally tested (temperature, vibration…).

Option (HS): Heat Sink

A heat sink (HS) can be provided to allow the operation of Power Amplifiers. Please note that most power amplifiers need heat sink or appropriate heat dissipation strategy.

Space / Hi-Rel Usage

Most of ERZIA´s products are based on rad-hard technologies and can be manufactured and integrated according to MIL / ECSS or specific hi-rel standard-screening for space, aeronautics, or specific hi-reliability usage.

Customization and Extended Performances

ERZIA can fully design or adapt one of the existing RF amplifiers designs according to your specifications. Please contact us for additional information.

Model Number Codification

MODEL NUMBER



ERZIA

20260818_rev1.1

Copyright © 2017 ERZIA Technologies. All rights reserved. This information is commercial and indicative, subject to change without notice

Tel: +34 942 29 13 42 sales@erzia.com www.erzia.com